



## **Product Code**

UTAS-2105 Core Drilling Machine on Trailer
UTGD-0330 Coring Bit for Asphalt 50 mm dia. x 400 mm length
UTGD-0332 Coring Bit for Asphalt 75 mm dia. x 400 mm length
UTGD-0334 Coring Bit for Asphalt 100 mm dia. x 400 mm length
UTGD-0336 Coring Bit for Asphalt 150 mm dia. x 400 mm length

## Standards

## EN 12697-27, ASTM D 5361

Portable UTAS-2105Core Drilling Machine is designed to cut cores up to 150 mm diameter from concrete, asphalt and similar hard construction materials.

The machine comprises a vertical support column which carries the drill head/ motor assembly. The motor assembly comprises a 6.5 hp petrol engine.

A ball screw mechanism enables close control of the drilling pressure and rapid return when drilling is completed. A water spraying assembly is mounted on the machine.

The drilling machine is installed in a trailer for fast and precise sampling on-site. 100 litre water tank provides continuous lubrication during drilling to save time.

The two-wheeler taut liner trailer is fully equipped with brake lamps/hazard lashers/retro reflectors conforming to road traffic regulations.

The trailer is designed with a space to be used for storing the core samples. The two fixing legs are robustly designed for improved stabilization.

Coring Bits should be ordered separately.

Dimensions	1520x2050x2050 mm
Weight (approx.)	300 kg
Power	6.5 hp



UTGD-0336

UTGD-0334

UTGD-0332 UTGD-0330



