



### Product Code

- UTW-0622 Electronic Analytical Balance, LCD Screen  
210 g x 0.0001 g
- UTW-0625 Electronic Analytical Balance 200 g x 0.001 g
- UTW-0628 Electronic Analytical Balance 300 g x 0.001 g
- UTW-0630 Electronic Analytical Balance 500 g x 0.001 g
- UTW-0631 Electronic Analytical Balance 820 g x 0.001 g
- UTW-0632 Electronic Analytical Balance 1000 g x 0.001 g

The UTW Series Electronic Analytical Balances set the standard in terms of reliable measurements, user-friendly and long service life. The balances can be used for routine tasks and/or complicated weighing procedures.

The UTW-0622, UTW-0625 and UTW-0628 models have an automatic internal calibration feature, the other models in the range require external calibration.

The UTW Series Analytical Balances provide fast and easy installation and cleaning with their ergonomic designs and brilliant displays. They can also be connected to printers or PC's through RS 232 outputs to give excellent monitoring and reporting performance.



UTW-0622

|          | Capacity | Readability | Pan Size | Additional Power Supply |
|----------|----------|-------------|----------|-------------------------|
| UTW-0622 | 220 g    | 0.1 mg      | Ø90 mm   | DC 12V (1,2A) Adapter   |
| UTW-0625 | 210 g    | 1 mg        | Ø115 mm  | DC 12V (1,2A) Adapter   |
| UTW-0628 | 300 g    | 1 mg        | Ø115 mm  | DC 12V (1,2A) Adapter   |
| UTW-0630 | 500 g    | 1 mg        | Ø115 mm  | DC 12V (1,2A) Adapter   |
| UTW-0631 | 820 g    | 1 mg        | Ø115 mm  | DC 12V (1,2A) Adapter   |
| UTW-0632 | 1000 g   | 1 mg        | Ø115 mm  | DC 12V (1,2A) Adapter   |

|          | Under-Bench Weighing Facility | Dimensions     | Weight (approx.) |
|----------|-------------------------------|----------------|------------------|
| UTW-0622 | No                            | 400x500x500 mm | 6 kg             |
| UTW-0625 | No                            | 250x250x300 mm | 2 kg             |
| UTW-0628 | Yes                           | 250x250x300 mm | 2 kg             |
| UTW-0630 | Yes                           | 250x250x300 mm | 2 kg             |
| UTW-0631 | Yes                           | 380x470x340 mm | 5 kg             |
| UTW-0632 | Yes                           | 380x470x340 mm | 5 kg             |